

## BioMax Hydraulic EAL

### ENVIRONMENTALLY ACCEPTABLE HYDRAULIC LUBRICANT

Royal Purple's BioMax Hydraulic EAL carries the Ecolabel certification identifying it as an Environmentally Acceptable Lubricant, recognized world-wide. This high-performance lubricant is specifically formulated for hydraulic systems used in environmentally sensitive areas including, but not limited to the applications below. The EU Ecolabel certification of BioMax guarantees superior environmental and technical standards.

Environmentally-friendly lubricants often compromise performance and durability in order to meet biodegradability and toxicity requirements. BioMax Hydraulic EAL provides uncompromised lubrication and protection for all hydraulic components requiring the use of an Environmentally Acceptable Lubricant. The performance advantage over competing oils is due to BioMax's superior formulation, using the highest quality synthetic base stocks and Royal Purple's proprietary Synerlec<sup>®</sup> additive technology. This unique, synthetic additive is proven to provide lasting protection and optimized efficiency.



#### APPLICATIONS

BioMax Hydraulic EAL is perfect for hydraulic systems operating in:

- Inland waterways, off-shore and blue-water marine equipment
- Wind turbine and other power generation equipment
- Construction and mining mobile and stationary equipment
- Forestry service equipment
- Wastewater treatment facilities

#### PERFORMANCE ADVANTAGES

- HIGH FILM STRENGTH - Synerlec<sup>®</sup> additive technology dramatically reduces metal-to-metal contact, friction, and wear
- EXCEPTIONAL CORROSION & RUST PROTECTION - Prevents internal damage to equipment from chemical attack
- SUPERIOR OXIDATION & THERMAL STABILITY - Resists oil degradation and varnish formation for longer oil life
- OUTSTANDING SYSTEM PERFORMANCE - Provides a wide operating temperature range and excellent shear stability
- EXCELLENT DEMULSIBILITY - Rapidly separates from water, allowing free water to be drained from the system
- OUTSTANDING ELASTOMER COMPATIBILITY - Will not harm seals designed for use with lubricating oils

#### SPECIFICATIONS AND APPROVALS

- EU Ecolabel License No. BE/027/004
- US EPA VGP (2013) and VIDA
- HS Marine (BioMax Hydraulic EAL 46)
- ISO 15380
- DIN 51524 Part 2
- Fives Cincinnati P-68, P-69, P-70

Typical Physical Properties					
Property	Test Method	22	32	46	68
Viscosity @ 0°C, cSt	ASTM D445	168.70	284.90	445.70	720.20
Viscosity @ 40°C, cSt	ASTM D445	22.00	32.00	48.00	68.00
Viscosity @ 100°C, cSt	ASTM D445	4.86	6.19	8.13	10.70
Viscosity Index	ASTM D2270	158	159	159	159
Density @15°C, g/ml	ASTM D4052	0.908	0.859	0.869	0.863
Demulsibility, ml/ml/ml	ASTM D1401	40/40/0	42/38/0	42/38/0	42/38/0
Copper Corrosion	ASTM D130	1A	1A	1A	1A
Rust Prevention, Dist. Water	ASTM D665A	PASS	PASS	PASS	PASS
Rust Prevention, Sea Water	ASTM D665B	PASS	PASS	PASS	PASS
Elastomer Compatibility	ISO 6072	PASS	PASS	PASS	PASS
Pour Point, °C (°F)	ASTM D97	-63 (-81)	-60 (-76)	-60 (-76)	-45 (-49)
Flash Point, °C (°F)	ASTM D92	246 (475)	233 (451)	233 (451)	231 (448)
Foam Tendency, Seq. I, II, III	ASTM D892	0/0	0/0	0/0	0/0
Dielectric Breakdown, kV	ASTM D877	43	48	49	47
Four-Ball Wear, mm	ASTM D4172	0.49	0.47	0.48	0.49
Four-Ball EP, LWI	ASTM D2783	37.6	54.2	56.9	57.4
Four-Ball EP, Weld Load, kg	ASTM D2783	200	200	250	250
FZG Gear Test, A/8.3/90	ASTM D5182	>12	>12	>12	>12
Biodegradability, % (28 days)	OECD 301B	>60	>60	>60	>60
Toxicity (Algae), mg/L	OECD 201	>1000	>1000	>1000	>1000
Toxicity (Daphnia), mg/L	OECD 202	>1000	>1000	>1000	>1000
Toxicity (Fish), mg/L	OECD 203	>1000	>1000	>1000	>1000
Toxicity (Bacteria), mg/L	OECD 209	>1000	>1000	>1000	>1000
Bioaccumulation, log POW	OECD 107	<3	<3	<3	<3

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name of use and whether there is any infringement of patents is the sole responsibility of the user.

© 2020 Calumet Specialty Products, LLC. All Rights Reserved.

Distributed By Calumet Branded Products, LLC | 2780 Waterfront Pkwy. E. Dr., Suite 200 | Indianapolis, IN 46214 | Technical Services: 888-382-6300 | www.royalpurple.com

7/29/2022