

HPS®

HIGH PERFORMANCE STREET MOTOR OIL

Product Description

Royal Purple® HPS® is specifically formulated to meet the demands and operating conditions of vintage, late-model, and modified high-performance engines. Whether addressing increased valvetrain loads from aggressive camshaft profiles or elevated power levels from forced induction and other performance enhancements, HPS® provides reliable protection for severe street and light competition applications.

Formulated with premium base oils, advanced Synerlec® technology, and optimized levels of ZDDP (zinc dialkyldithiophosphate), HPS® engine oils deliver exceptional wear protection and enhanced engine performance. Recommended for gasoline and light duty diesel engines—including turbocharged, supercharged, and naturally aspirated applications—HPS® also incorporates robust detergents and dispersants to control the formation of deposits, sludge, and varnish, helping maintain engine cleanliness and support efficient combustion. Not suitable for use in motorcycle or wet clutch applications.

Choose Royal Purple® HPS® for superior wear protection, performance, and cleanliness in both modified and stock street-driven vehicles.

PERFORMANCE ADVANTAGES

- **OUTSTANDING WEAR PROTECTION** – Industry leading anti-wear performance that provides protection and reduces metal to metal contact in your modified engine
- **MAXIMIZED ENGINE PERFORMANCE** – Greater lubricity and low coefficient of friction ensure maximum engine performance
- **EXCEPTIONAL OXIDATION STABILITY** – Slows the breakdown of oil to provide long lasting protection
- **SUPERIOR ENGINE CLEANLINESS** - Advanced synthetic solvency reduces engine deposits and keeps engines clean
- **INCREASED ENGINE PROTECTION** - Reduces Low Speed Pre-Ignition (LSPI) in turbocharged Gasoline Direct Injection (GDI) engines

PRODUCT DATA

Typical Properties						
Property	Test Method	HPS 5W-20	HPS 5W-30	HPS 10W-30	HPS 10W-40	HPS 20W-50
KV40, cSt	ASTM D445	46.73	59.4	61.29	95	151.1
KV100, cSt	ASTM D445	8.22	10.14	10.04	14.73	18.97
Viscosity Index	ASTM D2270	151	159	150	162	143
Cold Crank Simulator (CCS) cP	ASTM D5293	4949 (-30C)	5233 (-30C)	3963 (-25C)	5919 (-25C)	5205 (-15C)
TBN, mg KOH / g	ASTM D2896	7.48	7.03	7.24	7.34	7.39
Density	ASTM D4052	0.8502	0.8506	0.8521	0.8533	0.8633
Pour Point, C	ASTM D97	-42	-36	-36	-36	-33
Flash Point, F	ASTM D92	440	450	460	450	440

Distributed By:
 Calumet Branded Products, LLC
 1060 N Capitol Ave
 Suite 6-401
 Indianapolis, IN 46204
 Technical Services: 888-382-6300
 www.royalpurple.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name in use and whether there is any infringement of patents is the sole responsibility of the user.

All trademarks are owned by one or more affiliates within the Calumet, Inc. organization, unless otherwise specified.

The color purple is a registered trademark of Calumet Branded Products, LLC.

© 2026 Calumet Inc. All Rights Reserved.