

Engine Break-In Oil

PRODUCT DESCRIPTION

Royal Purple[®] Engine Break-In Oil is specifically formulated to provide outstanding wear protection while allowing a quick break-in period for newly built and rebuilt engines. Engine builders have grown increasingly concerned that current engine oils that are API licensed for new cars and trucks do not provide adequate wear protection for freshly built performance engines, particularly those using flat tappet camshafts and lifters. Royal Purple has addressed this issue with Royal Purple Engine Break-In Oil.

Royal Purple Engine Break-In Oil is formulated to provide the critical wear protection needed by the engine valve train and camshaft while allowing new piston rings to quickly seat to the engine cylinder walls. Engine Break-In Oil combines highly refined mineral base oils (preferred for engine break-in) with an advanced additive package containing elevated levels of zinc/phosphorus anti-wear additive to optimize wear protection during the sensitive engine break-in phase.

Royal Purple Engine Break-in Oil is a fully formulated conventional SAE 10W-30 engine oil and does not require the use of any other chemical additives. We recommend using Engine Break-In Oil for a minimum of 500 - 1,000 miles in street driven gasoline engines to assure that the piston rings are properly seated to the cylinder walls before switching to one of our full synthetic engine oils. If need be, you can use for up to 3,000 miles. Once break-in of the engine is complete, Royal Purple HPS[®] for street use and light competition, or Royal Purple XPR[®] for competition use (or simply to get the ultimate in performance and protection), are recommended.

FEATURES and BENEFITS

- ELEVATED ZINC/PHOSPHORUS ANTIWEAR ADDITIVE - Outstanding wear protection during the sensitive engine break-in phase
- HIGH-QUALITY MINERAL BASE STOCKS – Excellent lubricity while allowing quick seating of the engine piston rings
- EXCEEDS API SJ PERFORMANCE REQUIREMENTS* – Fully formulated and suitable for up to 3,000 miles of use.

**Unlicensed engine oil; exceeds performance requirements of API SJ specification.*

PRODUCT DATA

Typical Properties		
Property	Test Method	10W-30
Viscosity @ 40°C, cSt	ASTM D445	78
Viscosity @ 100°C, cSt	ASTM D445	12
Viscosity Index	ASTM D2270	149
Flash Point, °C (°F)	ASTM D92	204 (400)
Pour Point, °C (°F)	ASTM D97	-42 (-45)
Cold Crank Simulator, cP	ASTM D5293	4,854 @ -25°C
Base Number, mg KOH/g	ASTM D2896	9.1



TECHNICAL DATA SHEET

HEALTH and SAFETY

Health and safety recommendations for products can be found on the Safety Data Sheet (SDS) www.royalpurple.com

Distributed By:

Calumet Branded Products, LLC
1060 N Capitol Ave
Suite 6-401
Indianapolis, IN 46204
Technical Services: 888-382-6300
www.royalpurple.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name in use and whether there is any infringement of patents is the sole responsibility of the user.

All trademarks are owned by one or more affiliates within the Calumet, Inc. organization, unless otherwise specified.

The color purple is a registered trademark of Calumet Branded Products, LLC.

© 2026 Calumet Inc. All Rights Reserved.

8/4/2026